

REVO SC-2

PRODUCT DESCRIPTION

The REVO SC-2 preamplifier combines pure and elegant style with refined technology.

Entirely remote-controlled, the REVO SC-2 uses an exclusive volume control system called P.D.A.A. (Programmable Digital Analogue Attenuation).

It is realized only with discrete components, relays and precision resistors, and offers an attenuation range of 127.5 dB in 0.5 dB steps. Input and output selection is made by high quality relays.

Accordingly to Norma's own Sound Philosophy of best neutrality and transparency of signal treatment, the SC-2 offers the possibility to choose between Active and Passive mode.

(Easily operable also via Remote Control).

Disclaimer: Norma Audio reserves the right to change specification without notice.



GALLERY IMAGES



PRODUCT SPECIFICATIONS

Brand	Norma Audio
Input	4 RCA, 2 XLR Balanced, Optional Phono at INPUT 1
Input Impedance	47Kohm (not selected input) / 10 Kohm (Selected Input)
Input Configuration	Phono MM/MC, Line, Balanced, Multichannel & DAC option
Output	1 RCA, 1 XLR Balanced
Output Impedance	220 ohm
Output Voltage	7.5 V r.m.s.
Frequency Response	0 Hz – 2.0 MHz (-3dB, non filtered)
Gain	17.5 dB Active mode, 0 dB Passive mode
Circuitation	Solid state, Dual Mono, hi speed, low noise
Supply	230 V AC / 50 Hz (100V AC or 115 VAC / 50-60Hz in some countries)
Dimensions (HxWxD)	110 x 430 x 365 mm
Weight	15 Kg
Note	Stereophonic Preamplifier completely RC