

Certaldo

PRODUCT DESCRIPTION

Certaldo series 2 inherits the hybrid rear/down firing loading system of the previous version and further develops it.

Enclosure volume was increased around 10% and in order to obtain a greater low-end octave authority and reduced distortion the 5.25" midwoofers were re-engineered focusing on the motor venting system and suspension material.

An additional improvement was also provided by the underneath aluminium port with its redesigned and enlarged gradual flaring which contributed to the overall over-damped yet powerful bass performance.

Having demonstrated an excellent overall performance, we decided to reconfirm the 1" neodymium wide surround silk dome tweeter used in the previous Certaldo. Thanks to the implementation of an all-new crossover, this unit has found a second youth integrating in an even more linear way with the midwoofers.



GALLERY IMAGES



PRODUCT SPECIFICATIONS

Brand	Rosso Fiorentino
Type	2.5 -way rear/down firing ported floor standing system
Sensitivity	88 dBspl (2.83V, 1m)
Nominal impedance	8Ω (minimum 5Ω)
Recommended amplifier power	50W – 150W into 8Ω with unclipped sound signal
Cabinet	Solid HDF fibreboard, aluminium front and side panels, internal damping pads
Dimensions	Height: 1075mm (42.3 in) incl. plinth and spikes Width: 194mm (7.6 in) 237mm (9.3in) including plinth Depth: 262mm (10.3in) 303mm (11.9in) including plinth
Net weight	28 Kg (61.7 lb) each
Cabinet finish	Exclusive RF silky matt black coating

DRIVE UNITS

1 x ø 25mm (1 in) silk dome neodymium tweeter
1 x ø 130mm (5.25 in) glass fibre composite cone mid-range
2 x ø 130mm (5.25 in) glass fibre composite cone mid-woofer