

REVO IPA-150

PRODUCT DESCRIPTION

The characteristics of the REVO PA-150 make it an extremely versatile amplifier. The high power (150W / 80hm), the ability to drive even the most difficult speakers and the sound characteristics, make it a unique device. Power, dynamics, speed, transparency are combined with an absolute lack of listening fatigue and a marked musicality.

These features make it an ideal match with the REVO SC-2 preamplifier, which expresses the same sonic personality. But, even if you want to combine it with other preamps, the REVO PA-150will become a perfect partner. For example, with the best tube preamps you will be able to enhance the sonic peculiarities, giving an extraordinary ability to drive the speakers without introducing any harshness in the sound or listening fatigue, often present in solid state amplifiers.

Disclaimer: Norma Audio reserves the right to change specification without notice.



GALLERY IMAGES







PRODUCT SPECIFICATIONS

Brand	Norma Audio
Connections	1 RCA, 1 XLR Balanced
Input Impedance	47Kohm (not sel. Input) / 33Kohm (sel. Input)
Outputs Voltage	1 Binding Post couple, 4mm Banana and forks
Frequency Response	0 Hz - 2.0 MHz (-3dB, not filtered)
Output Power	150W RMS / 80hm - 280W RMS / 4 0hm (per channel)
Gain, Sensitivity	28.5 dB, 1.30 V rms / 150 W - 8 Ohm
Configuration	Dual Mono
Configuration	Solid state
Power devices	MosFet, 4 couple each channel
Available output current	48 A continuous, 200 A peak (each channel)
Capacity of filter	72.000 Uf, 12 capacity for each channel
Electric Transformers	2 toroidal special audio use, 400 VA each channel
Supply	230 V AC / 50 Hz (100V AC or 115 VAC / 50-60Hz in some countries)
Dimensions (HxWxD)	110x430x365mm (excluding footers and rear connections)
Weight	25 Kg
Notes	Stereophonic final amplifier

