

## REVO PA-160

### PRODUCT DESCRIPTION

The characteristics of the REVO PA-160MR make it a unique amplifier in the world panorama. ALL power supplies are electronically stabilized. The stabilized power stages have a speed and accuracy, orders of magnitude greater than those required by even the most dynamic musical signal.

The regulation characteristics are, in every parameter, much higher even than the best batteries, without however presenting the drawbacks. The "IDEAL POWER SUPPLY" was simply implemented, without any form of disturbance or pollution from the outside.

Listening to a pair of REVO PA-160MR it is illuminating about the hidden potential of high fidelity. Music, freed from this chronic pollution with which the enthusiast has always lived, finally finds the possibility of expressing itself towards a reproduction realism never before found.

In addition, power, dynamics, speed, transparency are combined with an absolute lack of listening fatigue and a marked musicality.

*Disclaimer: Norma Audio reserves the right to change specification without notice.*



### GALLERY IMAGES



**PRODUCT SPECIFICATIONS**

<b>Brand</b>	Norma Audio
<b>Connections</b>	1 RCA, 1 XLR Balanced
<b>Input Impedance</b>	47Kohm (not sel. Input) / 33Kohm (sel. Input)
<b>Outputs Voltage</b>	1 Binding Post couple, 4mm Banana and forks
<b>Frequency Response</b>	0 Hz - 2.0 MHz (-3dB, not filtered)
<b>Output Power</b>	160W RMS / 8Ohm - 300W RMS / 4 Ohm
<b>Gain, Sensitivity</b>	28.5 dB, 1.35 V rms / 160 W - 8 Ohm Topology Full Regulated Power Supply, High Speed, High Current Very Low Noise, Very Low Impedance
<b>Configuration</b>	Solid state Mono
<b>Power devices</b>	MosFet, 4 pairs
<b>Available output current</b>	48 A continuous, 200 A peak
<b>Capacity of filter</b>	72.000 Uf, 24 capacitors
<b>Supply</b>	230 V AC / 50 Hz (100V AC or 115 VAC / 50-60Hz in some country)
<b>Dimensions (HxWxD)</b>	110x430x365mm (excluding feet, rear connections)
<b>Weight</b>	25Kg
<b>Notes</b>	Monophonic power amplifier